

Perfect choice for Access Control

Akuvox's E18C is a safe and convenient commercial-grade device for both intercom & access control. With the latest deep learning algorithm and dual cameras liveness detection technology, E18C can be deployed in the field for community and commercial applications, for the implementation of smart access control.



At a Glance

- Visible light facial recognition;
- Dual cameras with anti-spoofing algorithm against photo and video attack;
- 20,000 face capacity & 20,000 card capacity;
- Face recognition duration less than 0.2s/user, face recognition accuracy rate greater than 99.5%;
- Allows both audio and video communication to an IP phone, mobile client, or softphone;
- Multiple verification methods including: face, PIN, cards NFC, BLE and QR codes;
- Stand-alone operation;
- Configuration via web browser;

Anti-epidemic Function

- Mask Detection
- Body Temperature Detection [Only E18C(MD02) support]

Physical & Power

- | | |
|---|--|
| • Housing Material: Plastic | • Ethernet Port: RJ45, 10/100Mbps adaptive |
| • Display: 7 Inch IPS LCD, 1024x600 | • Bluetooth: Support |
| • Camera: 2M pixels, WDR | • Reset: 1 |
| • Wiegand In: 1 | • 802.3af Power-over-Ethernet |
| • Wiegand Out: 1 | • 12V DC Connector (if not using PoE) |
| • RS485 Port: 1 | • Tamper: Support |
| • RF Card Reader: 13.56MHz,125kHz & NFC | • Installation: Wall-mounted |
| • Relay In / Out: 3 / 2 | • IP Level: IP65 |
| • TF Card Slot: 1 | • Working Humidity: 10~90%, no condensing |
| | • Working Temperature: -20°C~+55°C |
| | • Storage Temperature: -30°C~+60°C |

Identification

- Identification Mode: Face, PIN, NFC, RFID Card, BLE & QR code
- Identification Speed: < 200ms


Capacity

- Face Capacity: 20,000
- Card Capacity: 20,000
- Event Log: 50,000

Forehead Temperature Measurement

- Only E18C(MD02) support
- Distance: 0.3M ~ 1M
- Accuracy: 0.1°C
- Deviation: ±0.3°C
- Range: 34°C ~ 45°C

Dimensions



Application

