

SVC-SP10

In-Ceiling Mount HD IP Loudspeaker 15W



SVC-SP10

The Supervoice SVC-SP10 is a 15W in-ceiling mount HD IP loudspeaker, designed for public address announcement solutions in offices, schools, hospitals and many other locations. This IP speaker offers clear HD audio and it supports various SIP audio codecs such as OPUS, G711U, G711A, G722, GSM, MP3, WAV and more, as well as SIP & Multicast paging (10 Multicast addresses/channel). It can be paired with other IP devices and offers SIP security via TLS, Password protection, IP address filtering, Digest authentication, User access log etc.

Model Specifications

Audio

Protocol Decoding	OPUS (48KHz 8Kbps - 512Kbps Mono/Stereo), MP1 (44.1KHz 128Kbps Stereo), MP2 (44.1KHz 128Kbps Stereo), MP3 (44.1KHz 128Kbps Stereo), G.711 A-Law (8KHz 64Kbps), G.711 u-Law (8KHz 64Kbps), G.722 ADPCM (16KHz 64Kbps), Linear PCM 16bit Stereo 44.1KHz, Linear PCM 16bit Mono 44.1KHz, GSM (8KHz 13Kbps),MP3 ,WAV
Frequency Response	100Hz ~ 18KHz
Max SPL	96 dB

Network

VoIP Protocol	SIP, Multicast
Network Interface	10/100 Base-TX, RJ45
Security	Password protection, IP address filtering, Digest authentication, User access log

Messages

Pre Recorded Message Playback File Type	WAV - MP3
SIP Call Audio	Supported
Multicast Announcements	10 Multicast Addresses / Channel Supported

SIP

SIP Version	SIP V2
SIP Accounts	2 SIP Accounts
SIP Security	TLS
SIP Codecs	OPUS, G711U, G711A, GSM, MP3, WAV.

Amplifier

Build-in Amplifier	Class D - 15 Watt
--------------------	-------------------

Power

Rate Power	15 Watt
Power Supply	PoE or DC 12V/24V

Physical

Material	Metal
Installation Type	In Ceiling
Dimensions	200 x 90 mm
Weight	1 Kg
Operating Temperature	-30°C - +60°C
Operating Humidity	5% - 85%

Warantee

Basic Warranty	Bring In - 2 years
Warranty Expansion	Optional